

THERMOPLASTIC

Check Valves

MAIN FEATURES

- 1-1/4" MPT x 1-1/4" Barb or 1-1/2" slip ABS check valve
- Full port design
- Flapper opens 100%, a feature that sets this valve apart from any of the competition
- Maximum temperature 140°F

RATINGS

- Rubber boot installation: 10 feet of head / 4.3 psi
- Solvent weld installation: 58 feet of head / 25 psi

1 YEAR
LIMITED WARRANTY

MLP79507



MAIN FEATURES

- 1-1/2" MPT x 1-1/4" Barb or 1-1/2" slip ABS check valve
- Full port design
- Flapper opens 100%, a feature that sets this valve apart from any of the competition
- Maximum temperature 140°F

RATINGS

- Rubber boot installation: 10 feet of head / 4.3 psi
- Solvent weld installation: 58 feet of head / 25 psi

1 YEAR
LIMITED WARRANTY

MLP79509



MAIN FEATURES

- 1-1/2" MPT x 1-1/4" Barb or 1-1/2" slip PVC check valve
- Full port design
- Flapper opens 100%, a feature that sets this valve apart from any of the competition
- Maximum temperature 140°F

RATINGS

- Rubber boot installation: 10 feet of head / 4.3 psi
- Solvent weld installation: 58 feet of head / 25 psi

1 YEAR
LIMITED WARRANTY

MLP79549

