



SPECIFICATIONS



Shower Only Trim Kit - 11 Series


Shower Kit with 6" Arm and Flange, Single function Shower & Valve Trim – Requires M410 Rough-in Valve

Shower Head - MLR1FSHD

- 1/2" -14 NPSM Connection
- Self Cleaning Rubber Jets
- Single Function Spray
- Max Flow Rate: 1.8 GPM @ 60 PSI (6.8L/Min)
- 100% Factory Pressure Tested

Shower Arm & Flange - ML6SA & MLRSF

- 6" Shower Arm for Wall Mount Application
- Finished Metal Body
- 2 x ½" -14 NPT Connection
- Metal, 2 ½" Dia Round Shower Flange



- Includes Ceramic Disc Cartridge
- Requires Mainline M410 Rough-in Valve

Deep Installation Adapters (Optional)

• Easy – Press to Place Installation

JV11

Specified model meets or exceeds the following:

- ASME A112.18.1/CSA B125.1
- IAPMO/cUPC
- EPA WaterSense®
- ADA for lever handle control

AVAILABLE FORMATS

Multiple Kit Formats Available Visit mainlinecollection.ca

Mainline products have been manufactured under the highest standards of quality and workmanship. That is why we offer "Limited Lifetime" warranty on the function and finish of our shower faucets.



Standards & Certifications					
A TOP OF THE PARTY	NSF/ANSI 372 NSF/ANSI 61-9 UPC	COMPLIES WITH LEAD PLUMEING LAWS	F		

Available Finishes				
~			/	

Please **visit www.mainlinecollection.ca** for available finishes. Finish is defined by additional suffix. Please **visit www.mainlinecollection.ca** for detailed Specification of components.

SUBMITTAL INFORMATION

Name:	Contractor:	
Location:	Contact #:	
Notes:		